

DC OUTPUT (max 4000W) : 0 - 260 Amps
0 - 1500 Volts



Presentation :

- Specifications:
 - 19 inch rack or cabinet
 - Height : 3U
 - Depth: 380 mm
- Minimum volume and weight for maximum capacity
- Switched mode technology
- Voltage and current controlled by PWM (Pulse Width Modulation)
- On request : programmable voltage/current: 0-10 V, isolated to 1500 Vrms
- Over-voltage protection (OVP) / Over-temperature protection (OTP)
- Touch interface

Power : MX 4000W Weight : 15 Kg	
Volts	Amps
0 - 15	0 - 260
0 - 30	0 - 130
0 - 50	0 - 80
0 - 75	0 - 53
0 - 100	0 - 40
0 - 150	0 - 26
0 - 180	0 - 22
0 - 250	0 - 16
0 - 350	0 - 11
0 - 750	0 - 5
0 - 1200	0 - 3
0 - 1500	0 - 2

Stabilized laboratory power-supply TACTILE MICROLAB DC MX 4000W

Descriptions :

- . Polycarbonate front panel
- . Two modes of operation: constant current (CC) and constant voltage (CV) indicated by two LEDs
- . Power output activated by pressing 'OUT'
- . Power input by standardised pluggable connector
- . Power outputs on insulated terminals or screw terminal block

Power : MX 4000W
Weight : 15 Kg

AC Input

Voltage	400 Vac Triphase
Power factor	> 0,95

DC Output

Power	4000 W
Voltage	0 to 1500 V
Current	0 to 260 A
Mode of operation	CV-CC
Residual ripple	< 0,5% of the normal gauge
Accuracy (voltage and current)	< 0,2% of the normal gauge
Stability	< 0,2% of the normal gauge
Linearity	< 0,2% of the normal gauge
Distortion	< 0,5%

Environment

Temperature	0 to +40°C (55°C derating)
Relative Humidity	85% without condensation
Cooling	Controlled air cooling
Dielectric Rigidity	1500 Vrms

Customisation :

Digital control:

- 2-wire RS 485 / Ethernet / Wifi
- Profibus DP
- Standard : Schneider/ Siemens/Wago/Phoenix...

Analog control:

- U and I Inputs/Outputs
- 0-10V or 4-20 mA isolated 1500 Vrms


Polarity Inverter

A-h T.J.P Counter

Tension or Intensity Ramp

Timer

15-pin D-Sub connector for remote programming



Non-binding document, may be amended without notice.
Ref: 201218 / Tactile MX 4000W